Honeywell
THE POWER OF CONNECTED

Performance Series IP

HBW2PER1

Network WDR 2MP IR Bullet Camera

OPERATIONAL	
VIDEO STANDARD	NTSC/PAL
SCANNING SYSTEM	Progressive
IMAGE SENSOR	1/2.8" 2Megapixel progressive CMOS
NUMBER OF PIXELS (H × V)	1920(H) x 1080(V)
MINIMUM ILLUMINATION	0.07lux/F2.0(color,30IRE) 0Lux/F2.0(IR on)
S/N RATIO	More than 45dB
ELECTRONIC SHUTTER SPEED	1/3~1/100000s
IR DISTANCE	Up to 30m (98ft), depending on scene reflectance
IR LIGHT CONTROL	Manual/SmartIR/OFF
IR LIGHT NUMBER	18
DAY/NIGHT	Auto(ICR) / Color / B&W
BACKLIGHT COMPENSATION	BLC / HLC / WDR
WHITE BALANCE	Auto/Natural/Street Lamp/Outdoor/Manual/ Customized Region
GAIN CONTROL	0~100
WIDE DYNAMIC RANGE	120dB
NOISE REDUCTION	3D DNR
PRIVACY MASKING	Off / On (4 Areas, Rectangle)
MOTION DETECTION	Off / On (4 Zones, Rectangle)
REGION OF INTEREST	Off / On (4 Zones)
LENS	3.6mm Fixed, F2.0
ANGLE OF VIEW	H:88°, V:48°
VIDEO	
VIDEO COMPRESSION	H.265/H.264H/Smart Codec/MJPEG (Sub Stream)
RESOLUTION	1080P (1920×1080)/1.3M (1280×960)/ 720P (1280×720)/D1(704×480/576)/ VGA (640×480)/CIF(352×240/288)
FRAME RATE	Main Stream: 1080P(1 ~ 25/30fps) Sub Stream: D1(1 ~ 25/30fps)
BIT RATE CONTROL	CBR/VBR
BIT RATE	H.265: 12K ~ 6400Kbps H.264: 32K ~ 10240Kbps

NETWORK	
ETHERNET	RJ-45 (10/100Base-T)
SUPPORTED WEB BROWSERS	Internet Explorer (11.0+)
SUPPORTED OS	Windows® 7 32-bit/64-bit; Windows® 10 32-bit/64-bit
PROTOCOLS*	HTTP; HTTPs; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; DHCP; DNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS
INTEROPERABILITY	ONVIF Profile S/Q
MAXIMUM USERS ACCESS	20 Users
SECURITY	User account and password protection HTTPS, IP Filter, Digest authentication, User access log, TLS1.2 only, AES-128/256, SSH/Telnet closed, sFTP by default, PCIDSS compliance
EVENT	Network disconnection, IP conflict, Illegal access
ELECTRICAL	
POWER SUPPLY	DC12V, PoE (802.3af) (Class 0)
POWER CONSUMPTION	<5.2W
MECHANICAL	
DIMENSIONS	Ø70mm×164.7mm (2.76"x6.49")
PRODUCT WEIGHT	0.38kg (0.84lb)
PACKAGE WEIGHT	0.5kg (1.1lb)
MATERIAL	Metal+Plastic
CONSTRUCTION COLOR	RAL9003 (White)
ENVIRONMENTAL	
OPERATING TEMPERATURE	-30° C ~ +60° C (-22° F ~ +140° F)
RELATIVE HUMIDITY	Less than 95%, non-condensing
INGRESS PROTECTION	IP66
REGULATORY	
EMISSIONS	FCC Part 15B, EN 55032
IMMUNITY	EN 50130-4
SAFETY	UL 60950-1, EN 62368-1
ROHS	EN 50581

* Some development may be required in specific user cases to support some of these protocols in the field as they mature over time.

Network WDR 2MP IR Bullet Camera

RECOMMENDED ACCESSORIES

SYSTEM COMPATIBILITY	
HEN*4	8/16/32/64-channel Performance Series 4K NVRs (H.264 and H.265)
HEN*3	4/8/16/32-channel Performance Series 4K NVRs (H.264 and H.265)
HEN*2	4/8/16-channel Performance Series NVRs (H.264)
HRHT4*	4/8/16-channel 4 MP HQA/IP/CVBS Hybrid DVRs (H.264)

MOUNTS AND ACCESSORIES		
HB34S2-CM		Corner Mount Adapter
HQA-PM2		Pole Mount Adapter
HBS2-BB		Junction Box

ORDERING

HBW2PER1	Network WDR 2MP IR Bullet Camera, 1/2.8" CMOS, 3.6mm Fixed, 18 IR LEDs, PoE, IP66, H.265/H.264/Smart Codec

DIMENSIONS



For more information
www.honeywell.com/security

Honeywell Commercial Security
Aston Fields Road
Whitehouse Industrial Estate
Runcorn, Cheshire
WA7 3DL
Tel: +44 (0)8448 000 235

Honeywell Security Office
Emaar Business Park, Sheikh Zayed Road
Building No. 2, 2nd floor, 201
Post Office Box 232362
Dubai, United Arab Emirates
Tel: +971 44541704
www.honeywell.com

ONVIF and the ONVIF logo are trademarks of ONVIF Inc. Honeywell reserves the right, without notification, to make changes in product design or specifications.

HSV-HBW2PER1-01-UK(0119)DS-E
© 2019 Honeywell International Inc.

Honeywell