LigoWave

LigoPoE AC to 48V af/at adapter

100 – 240 AC to PoE 48V 802.3af/at adapter

COPYRIGHT © 2015 LigoWave

LigoPoE AC to 48V af/at adapter

The adapter is used to power 802.3af compatible devices like LigPTP PRO and UNITY from standard AC power source.

Electrical specification

Input voltage	100 – 240 VAC, 50/60 Hz
Output voltage	48 VDC +/- 5%
Output power	24 W
Output PoE type	802.3af/at on 1,2,4,5(+) and 3,6,7,8(-) pins
Data rate	1000 Mbps
Protection	Short circuit, Overvoltage, Overcurrent

Physical specifications

Input jack	IEC320 C6
Output jack	RJ45
Data jack	RJ45
Dimensions	123 x 60 x 39 mm
Weight	190 g
Operating temperature	-10 to +50 C
UTP/FTP cable length	100 m total (from switch to LigoPTP device)

Connection scheme

LigoWave

LigoPoE AC to 24V adapter

Copyright © 2015 LigoWave. All rights reserved. LigoWave and the LigoWave logo, are trademarks of LigoWave. All other company and product names may be trademarks of their respective companies. While every effort is made to ensure the information given is accurate, LigoWave does not accept liability for any errors or mistakes which may arise. Specifications and other information in this document may be subject to change without notice.
To learn more about LigoWave products, visit www.ligowave.com.